



ESTIMATED QUANTITIES FOR REINFORCING STEEL

BAR NO.	SIZE	SPAC.	LENGTH	WEIGHT
G	7 #4	SHOWN	13'-9"	64
H	5 #4	1'-8"	4'-6"	15
J	6 #4	8"	5'-0"	20
TOTAL WEIGHT*				99
CONCRETE FOR FOUNDATION*				C.Y. 0.47
CONCRETE FOR GUTTER DEPRESSION* C.Y. 0.78				
STRUCTURAL STEEL FOR ARMOR CURB SLOT				
STUD ANCHORS (2" DIA.)				LBS. 3.5
STEEL PLATE				LBS. 451
TOTAL WEIGHT*				LBS. 454.5

GENERAL NOTES:
 ALL CONCRETE SHALL BE CL 4".
 ALL DIMENSIONS RELATING TO REINFORCING STEEL ARE TO FACE UNLESS NOTED OTHERWISE.
 ALL SIDES OF ARMOR CURB SLOT AND STUD ANCHORS SHALL BE 2" FILET WELDS.
 ALL EXPOSED STRUCTURAL STEEL (ARMOR) SHALL BE GALVANIZED.
 ALL EXPOSED EDGES ON ARMOR CURB SHALL RECEIVE A 2" BEVEL.
 THE SHAPE OF THE TYPICAL ROADWAY CURB SHALL TRANSITION TO THE ARMOR CURB AS APPROVED BY THE ENGINEER.

ARMOR CURB SLOT WITH CONCRETE FOUNDATION
 SAN ANTONIO DISTRICT STANDARDS
 © 1998 Texas Department of Transportation
 TEXAS STATE HIGHWAY DEPARTMENT
 10/95
 REV 07/01